

System Engineering Report

Dr. Javier Marti ALMA Lead System Engineer




ASAC - Feb 28, 2011

1



JAO Construction organigram




ASAC - Feb 28, 2011

2



SE Activities





Facilitation of Engineering activities Focusing on key issues

Top10 Issues initiative

Top10 Priority	Key	Summary	Assignee	Reporter	Status	Res
1	TOP-35	System - Timing Event errors	Maurizio Miccolis	Javier Marti-Canales	A Open	UNF
1	TOP-31	System - Tuning and locking not sufficiently reliable	Nick Whyborn	Javier Marti-Canales	4 Open	UNF
1	TOP-23	Software - System robustness: tolerance to hardware failures	Brian Glendenning	Javier Marti-Canales	- Open	UNF
1	TOP-17	FE Calibration Devices. Reliability and "blocked motor" issues.	Juan Pablo Garcia	Javier Marti-Canales	Open	UNF
1	TOP-12	DV antennas - ACU connection lost, drive systems drop-out, brakes come on, etc	Jeff Zivick	Javier Marti-Canales	Closed	Fixe
1	TOP-10	DV antennas - Drifts and/or steps in zero points of inclinometers which produce large pointing offsets	Art Symmes	Javier Marti-Canales	Open	UNF
1	TOP-3	Grounding and electrical situation in the AOS building, including lightning protection	Patricio Garcia	Javier Marti-Canales	a In Progress	UNF
2	TOP-37	DV antennas - drive amplifier drop-outs	Art Symmes	Javier Marti-Canales	Open	UNF
2	TOP-36	DV antennas - encoder reports error state	Art Symmes	Javier Marti-Canales	Open	UNF
2	TOP-29	Software - Correlator	Brian Glendenning	Javier Marti-Canales	Closed	Fixe
2	TOP-28	Software - Control of focus and pointing offsets not complete	Brian Glendenning	Javier Marti-Canales	Closed	Fixe
2	TOP-27	Software - Archive reliability, efficiency and ease of use of the archive	Joseph Schwarz	Javier Marti-Canales	a Open	UNF
2	TOP-25	Software - Telescope Control and Monitor Data Base	Ravinder Bhatia	Javier Marti-Canales	a Open	UNF
2	TOP-22	Software - System robustness: reliable start-up	Gianni Raffi	Javier Marti-Canales	Open	UNF
2	TOP-13	DV antennas - Shutters tend to jam	Jeff Zivick	Javier Marti-Canales	2 Closed	Fixe
2	TOP-5	HVAC in the OSF control room needs to work and be quiet	Fabio Biancat Marchet	Javier Marti-Canales	Open	UNF
2	TOP-2	Reliability, quality and quantity of the power	Richard Kurz	Javier Marti-Canales	Open	UNF
3	TOP-30	Software - Data rate limitations	Brian Glendenning	Javier Marti-Canales	Open	UNF
3	TOP-14	DV antennas - Stow pins	Jeff Zivick	Javier Marti-Canales	Closed	Fixe
3	TOP-8	Membrane - Standing Waves	Ravinder Bhatia	Javier Marti-Canales	Open	UNF
3	TOP-1	Timely delivery and acceptance of complete antenna stations with power, communications, inserts, etc	Volker Heinz	Javier Marti-Canales	Closed	Fixe
	TOD 24	Control Phase forms	Desir Deducts	Indea Madi Canalas	0 0	1.15.17



Facilitation of Engineering activities Monitoring & Control and Alarms

- System level architecture of M&C to address operations, diagnostics, maintenance and safety needs
- Work roadmap in coordination with all players
 - Definition of M&C signals for array and infrastructure
 - Definition of required sampling and archiving frequency
 - Update of existing ICDs
 - Definition and implementation of system Alarms and Reduction Rules
 - Implementation by Computing

ASAC - Feb 28, 2011



System Verification (SV)

- System Requirements are flown down from Scientific Requirements
- SV Needs:
 - Quantify the extent of compliance of the ALMA System (Array + Infrastructure) performance with respect to original requirements
- This is an engineering task performed in intimate collaboration with scientists
- Progressive verification campaign as system is growing
 - 10% completed, 26% on-going
 - amplitude gain and phase long term (300sec) stability
 - bandpass stability

ASAC - Feb 28, 2011

	*										
	¥	A	В	С	D	E					
A	E	SYSREQ	215				M	N	0		
	System Veri	Parameter	Optics: Beam shape stability	BACK TO SUMMARY			Time	Line	11		
	Matrix	Requirements	Beam shape measurable and repeatable to:			157765030100					
SYS Reqt#	Parameter		< 1% of the peak at -10dB point for <400GHz and					2011			
			< 2% of the peak at -10dB point for >400GHz				R APR	MAY	JUN		
100 120	Ant: Number Ant: Diameter		under all operating conditions.								
130	Ant: Aperture Ef_	Related SCI	SCI-270								
131	Ant: Surface Ac Ant: Forward Ef	Remarks	Spec refers to the peak variation in time from the time average of the beam shape for								
132 134	Ant: Geometric L		each antenna; time period is 180 days.								
140	Ant: Offset Poin	Verification Type	T								
151	Ant: Delay error	Instrument	Inter								
	time, drift	Task	3-3								
152	Ant: Delay error time, noise	Procedure	(a) Measure stability of beam shape and gain using interferometric beam cuts for a								
154	Ant: Phase Cen		range of environmental conditions (temperature, solar illumination, wind) and elevation.						•		
	stability		All bands and both polarizations.								
161 162	Ant: nutator, nur Ant: nutator, per		(b) One enterne continuously tracks on unnelestrad point course whilet the enterne								
			(b) One antenna continuously tracks an unpolarized point source whilst the antenna under test does beam cuts.								
164	Ant: Number Sta		under test does beam cuts.								
165	Ant: Number St		(c) Long term repeatability (~ 180 days?) is verified by comparison between 2 beam								
1 1 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2	array		maps measured 180 days apart.								
205	Ontics: Boom S	Links to procedure	AIV-224				٠		ļ		
207	Optics: Aperture	Status	Ongoing								
210	Allignment (NEV Freq Coverage:	Cicioo	ongoing .								
215	Optics: Beam st		(a) AIV team measured beam stability during Station-3. The results are included in								
100000000000000000000000000000000000000	100		AIV station-3 reports.								
220	Receiver Noise		5 - 10 measurements / antenna. El range [20-60deg]. Jupiter/Mars.					•••••	····		
224	Optics: ON-axis		RX = B3, B6, B7, 1/4 Beam sampling.								
	polarization		Measurements & Reduction are done by D. Barkats's scripts.								
225	Optics: OFF-ax		Current conclusion: "Almost Pass" for B3 and B6.								
1783	polarization										
			For higher frequencies (>= B7), interferometric beam measurements at AOS are								
			desirable. CSV aims to do this systematically for all antennas and also every few								
226	Polarization: IF		months. Discussion with CSV-ANT team is needed.								
227	Signal Dynamic		(b) and (c) have not been done yet.								
231	1st Mixer Sideb	Links to status									
100		_	AIVC Processing Reports								
233	Front End: Conv	Applement Toom	ANV or OOV ANT				-				
201	Front End: IE or	Assigned Team	AIV or CSV-ANT						ļ		
234	Front End: IF O	Person SE/SV	KI. Morita / M. Sugimoto								
		Person Others	K. Tachihara								
							-				



Reliability (1/2)

- Needs:
 - Lifetime Observatory 30+ yrs
 - 66 antennas each with more than 500 LRUs each
 - Thousands of electronic boards on two Correlators
 - Stable interaction Hardware Software
- Still in an early integration phase
 - Infant mortality
 - Design flaws
 - Unexpected
 - Gaining experience



Reliability (2/2)








www.almaobservatory.org

The Atacama Large Millimeter/submillimeter Array (ALMA), an international astronomy facility, is a partnership among Europe, North America and East Asia in cooperation with the Republic of Chile. ALMA is funded in Europe by the European Organization for Astronomical Research in the Southern Hemisphere (ESO), in North America by the U.S. National Science Foundation (NSF) in cooperation with the National Research Council of Canada (NRC) and the National Science Council of Taiwan (NSC) and in Japan by the National Institutes of Natural Sciences (NINS) in cooperation with the Academia Sinica (AS) in Taiwan. ALMA construction and operations are led on behalf of Europe by ESO, on behalf of North America by the National Radio Astronomy Observatory (NRAO), which is managed by Associated Universities, Inc. (AUI) and on behalf of East Asia by the National Astronomical Observatory of Japan (NAOJ). The Joint ALMA Observatory (JAO) provides the unified leadership and management of the construction, commissioning and operation of ALMA.

ASAC – Feb 28, 2011 10



Organization of SE



ASAC - Feb 28, 2011

11